



## HT2

The machine is suitable for small and medium sized components. The HT2 machine has been designed to be simple to operate and highly efficient.



Capacity		Overall dimensions in mm/ inch			Trough dimension in mm/ inch after lining			Max Motor Power (kW / rpm)
Cu. Ft.	Litres	Length	Width	Height	Length	Width	Height	
2	60	825 / 32.5	725 / 28.5	971 / 38.2	575 / 22.6	395 / 15.5	368 / 14.5	0.34 / 1500 0.50 / 3000

Sizes indicated above are standard. Custom sizes can be manufactured to suit specific applications.

## Key Features

- ✓ Single phase connectivity.
- ✓ Wear resistant polyurethane lining.
- ✓ Very quiet in operation (noise level 65 db; this can vary based on process parameters).
- ✓ Compact design.
- ✓ Low profile for portability and storage.
- ✓ Easy to move around as it is mounted on castor wheels.
- ✓ The dosing pump can output 10L/h and is accessible by an access hatch at the rear of the machine.
- ✓ Independent recirculation system and integrated water filtration. The tank maximum capacity is 30L. It is recommended that only 25L of water and compound to be pre-mixed.
- ✓ Drive system with sealed bearings for maintenance-free running.

## Applications

Deburring  
Descaling  
Degreasing & Oil Rem  
Cleaning

Smoothing  
Radiusing  
Brightening & Polishing  
Burnishin

